

Exclusively from your Caterpillar® dealer



GEH275-2 (3-Phase)

50 HZ

STANDBY 275 kVA / 220 kW

PRIME 250 kVA / 200 kW

FEATURES

GENERATING SET

- Complete system designed and built at ISO9001 certified facility
- Factory tested to design specifications at full load conditions
- Fully engineered with a range of options and accessories

ENGINE

- Industrial water cooled diesel engine
- Isochronous electronic speed control
- Governor, electronic
- Electrical system, 24 VDC
- Cartridge type fuel and oil filters
- Air filter
- Lube oil drain valve
- Battery(ies), rack and cables

GENERATOR

- Self excited brushless generator
- Insulation system, class H
- Drip proof generator air intake (IP23)
- Electrical design in accordance with BS5000 Part 99, IEC60034-1, VDE0530, UTE51100

CONTROL SYSTEM

- PowerWizard 1.0 control panel
- Vibration isolated sheet steel enclosure with hinged lockable door

MOUNTING ARRANGEMENT

- Heavy-duty fabricated steel base with lifting points
- Anti-vibration pads to ensure vibration isolation
- Engine coupled to generator with flexible disc-coupling
- Baseframe incorporates heavy-duty fabricated steel fuel tank, 8 hours running capacity

EXHAUST SYSTEM

- Heavy duty industrial capacity exhaust silencer (approximately 10 dB reduction) supplied loose

COOLING SYSTEM

- Standard ambient temperatures up to 50° C (122° F)
- Fan, fan drive and charging alternator fully guarded
- Coolant drain valve
- Antifreeze protection coolant

CIRCUIT BREAKER

- 3-pole miniature circuit breaker (mcb) < 160 amps and 3-pole molded case circuit breaker (mccb) >= 160 amps
- Vibration isolated sheet steel enclosure with removable cover plate
- Outgoing cable stub-up area directly below circuit breaker

AUTOMATIC VOLTAGE REGULATOR

- Voltage regulation ±0.5 %
- Provides fast recovery from transient load changes

EQUIPMENT FINISH

- All electroplated hardware
- Anticorrosive paint protection
- High gloss polyurethane paint for durability and scuff-resistance

QUALITY STANDARDS

- BS4999, BS5000, BS5514, IEC60034, VDE0530

DOCUMENTATION

- Operation and maintenance manuals provided
- Wiring diagrams included

WARRANTY

- All equipment carries full manufacturer's warranty

Exclusively from your Caterpillar® dealer

OPTIONAL EQUIPMENT*

Engine	Droop engine control module for synchronising purposes Lube oil drain Lube oil drain pump High lube oil temperature shutdown
Generator	Anti-condensation heater Quadrature droop upgrade Permanent magnet generator (PMG) AREP Excitation system
Cooling System	Coolant heater Low coolant temperature alarm Low coolant level shutdown Radiator transition flange Coolant drain
Fuel System	Extended capacity metal basetank Manual fuel pump Low fuel level shutdown Low fuel level alarm High fuel level alarm Remote fuel systems Manual Bypass Valve
Silencer System — Open Unit	Level 2 silencer with mounting kit (approximately 25 dB reduction) Level 3 silencer with mounting kit (approximately 35 dB reduction) Overhead mounting kit for level 1 silencer Level 1, 2 and 3 silencer installation kits
Enclosures	Sound attenuated (EC) canopy
Handling/Trailers	Oil field skid
Controls	Baseframe mounted terminal box instead of control panel PowerWizard 2.0 control panel 6000 Series digital synchronising control panels
Remote Annunciators	PowerWizard annunciator
Circuit Breaker	Upgrades from 3-pole to 4-pole breaker
Transfer Switches	TM Series manual load transfer panels TC Series automatic load transfer panels ATI Series load transfer panels
Certification	European CE certification

*Some options may not be available on all models.
 Not all options are listed.

Consult your Olympian representative for more information

Exclusively from your Caterpillar® dealer

SPECIFICATIONS



GENERATOR

Make Olympian
 Model LL5014J
 Type Self-excited, brushless
 Voltage regulation ±0.5% at steady state from
 no load to full load
 Frequency ±0.25% for constant load from
 no load to full load
 Waveform distortion THD <4%
 Radio interference Compliance with EN61000-6
 Telephone Interference TIF <50, THF <2%
 Overspeed limit 2250 rpm
 Insulation Class H
 Temperature rise Within Class H limits
 Deration Consult factory for available outputs





ENGINE

Manufacturer Perkins
 Model 1306C-E87TAG6
 Type 4-Cycle
 Aspiration Turbocharged air to air charge cooled
 Cylinder configuration In-line 6
 Displacement — L (cu in) 8.7 (530.9)
 Bore/stroke — mm (in) 116.6/135.9 (4.6/5.4)
 Compression ratio 16.9:1
 Engine speed — rpm
 50 Hz 1500

Piston speed — m/sec (ft/sec)
 50 Hz 6.8 (22.3)
 Maximum power at rated rpm — kW (hp)
 Standby
 50 Hz 250.9 (336)
 Prime
 50 Hz 228.5 (306)
 BMEP — kPa (psi)
 Standby
 50 Hz 2306 (334.4)
 Prime
 50 Hz 2099 (304.5)
 Regenerative power — kW (hp)
 50 Hz 20.8 (27.9)
 Governor
 Type Electronic
 Class ISO 8528 G2

GENERATING SET DIMENSIONS AND WEIGHTS



Model	Length mm (in)	Width mm (in)	Height mm (in)	Weight* kg (lb)
GEH275-2	2960 (116.5)	1003 (39.5)	1718 (67.6)	2252 (4965)

Note:- General configuration not to be used for installation. See general dimension drawings for detail.

*Includes oil and coolant

Consult your Olympian representative for more information

Exclusively from your Caterpillar® dealer

GEH275-2 (3-Phase)

Generator Set Technical Data		50 Hz	
		Standby	Prime
Package Performance Power rating	kVA (kW)	275 (220)	250 (200)
Lubricating System Type: Wet sump Oil filter: Spin-on, full flow Oil cooler: Water Oil type required: API CG4 15W-40 Total lube system capacity Oil pan capacity	L (U.S. Gal) L (U.S. Gal)	26.4 (7.0) 22.7 (6.0)	
Fuel System Fuel Tank Capacity Generator set fuel consumption** 100% load 75% load 50% load	L (U.S. Gal) L/hr (U.S. g/hr) L/hr (U.S. g/hr) L/hr (U.S. g/hr)	350 (92.5) 63.3 (16.7) 50.2 (13.3) 34.3 (9.1)	58.9 (15.6) 46.1 (12.2) 31.1 (8.2)
Engine Electrical System Voltage/ground: 24 vDC/negative Battery charging alternator ampere rating	amps	45	
Cooling System Water pump type: Centrifugal Cooling system capacity Maximum coolant static head Coolant flow rate Minimum temperature to engine Temperature rise across engine Heat rejected to coolant at rated power Total heat radiated to room at rated power Radiator fan load	L (U.S. Gal) m H ₂ O (ft H ₂ O) L/hr (U.S. gal/hr) °C (°F) °C (°F) kW (Btu/min) kW (Btu/min) kW (hp)	45.3 (12.0) 13.0 (42.7) 13260 (3503) 79.0 (174) 5.0 (9.0) 110 (6256) 44.0 (2502) 10.3 (13.8)	103 (5858) 40.0 (2275)
Air Requirements Combustion air flow Maximum air cleaner restriction Radiator cooling air External restriction to cooling airflow Generator cooling air	m ³ /min (cfm) kPa (in H ₂ O) m ³ /min (cfm) Pa (in H ₂ O) m ³ /min (cfm)	16.4 (579) 6.2 (25.0) 424.2 (14980) 125 (0.5) 25.8 (911)	
Exhaust System Maximum allowable backpressure Exhaust flow at rated power Exhaust temperature at rated power (dry exhaust)	kPa (in Hg) m ³ /min (cfm) °C (°F)	10.7 (3.2) 44.5 (1572) 528 (982)	44.5 (1572) 500 (932)
Generator Set Noise Rating* (without attenuation) at 1 m (3.28 ft)	dBA	100.4	

*dBA levels are for guidance only

**Fuel consumption data at indicated load with diesel fuel with a specific gravity of 0.85 and conforming to BS2869:1998 Class A2.

Generator Technical Data	50 Hz						
	415/240V	400/230V	380/220V	230/115V	220/127V	220/110V	200/115V
Motor Starting Capability:							
Self Excited (kVA)	623	585	536	585	686	536	585
AREP Excited*** (kVA)	746	701	642	701	822	642	701
PM Excited**** (kVA)	746	701	642	701	822	642	701
Full Load Efficiency							
Standby %	92.9	93.1	93.1	93.1	92.9	93.1	93.1
Prime %	93.1	93.3	93.4	93.3	93.1	93.4	93.3
Reactances (per unit)							
Saturated X _d	2.69	2.90	3.21	2.90	2.39	3.21	2.90
X _d '	0.12	0.13	0.15	0.13	0.11	0.15	0.13
Reactances are shown X _q	0.073	0.079	0.088	0.079	0.065	0.088	0.079
X _q	1.61	1.74	1.93	1.74	1.44	1.93	1.74
applicable to the standby rating X _q	0.091	0.098	0.109	0.098	0.081	0.109	0.098
X ₂	0.082	0.088	0.097	0.088	0.072	0.097	0.088
X ₀	0.005	0.005	0.006	0.005	0.004	0.006	0.005
Time Constants:	t' _d	t''	t' _{do}	t _a			
	100 ms	10 ms	2175 ms	15 ms			

With AREP Excited Option AR20A/AR21A *With PMG Excited Option AR18A/AR19A

Consult your Olympian representative for more information

Exclusively from your Caterpillar® dealer

RATINGS AT AVAILABLE VOLTAGES

50 Hz					
Voltage Code	Voltage	Standby		Prime	
		kVA	kW	kVA	kW
VOPT502	415/240	275	220	250	200
VOPT503	400/230	275	220	250	200
VOPT504	380/220	275	220	250	200
VOPT506	230/115	275	220	250	200
VOPT507	220/127	275	220	250	200
VOPT508	220/110	275	220	250	200
VOPT510	200/115	275	220	250	200

Ratings at 27° C (80° F), 152.4 m (500 ft), 60% humidity, 0.8 pf

RATING DEFINITIONS

STANDBY

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. When used at standby rating the alternator will be peak continuous rated (as defined in ISO8528-3).

PRIME POWER

These ratings are applicable for supplying continuous power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Consult your Olympian representative for more information

5 0 H z

S T A N D B Y
P R I M E

2 7 5 k V A / 2 2 0 k W
2 5 0 k V A / 2 0 0 k W

OLYMPIAN™

Exclusively from your Caterpillar® dealer

Market: International

LEHF7209-00 (06/07)

Information contained in this publication may be considered confidential.
Discretion is recommended when distributing.

Materials and specifications are subject to change without notice.
CAT, CATERPILLAR, their respective logos and "Caterpillar Yellow", as well as corporate and product
identity used herein, are trademarks of Caterpillar and may not be used without permission.

www.CAT-ElectricPower.com

© 2007 Caterpillar
All rights reserved.
Printed in U.S.A.